

Submittal

NEOPRENE Sponge Rubber Joint Material



Neoprene

Description:

This product is a Closed-Cell Neoprene Sponge expansion joint filler. It is the ultimate solution for masonry expansion joints for brick and block. J & K Foam Fabricating, Inc.'s Neoprene meets and exceeds all ASTM D 1056 specifications for Closed Cell Sponge Neoprene expansion joints in residential, commercial, and industrial applications. Neoprene Sponge Rubber is available in multiple densities/types to meet a wide range of specifications.

Use:

Neoprene helps prevent clogging of expansion joint with mortar and is the accepted material for brick and block expansion joint fillers. It can be used in almost any residential, commercial or industrial application. Neoprene can be custom cut for your jobsite needs and is available with or without PSA (Pressure Sensitive Adhesive)

Features

- A high quality, closed cell neoprene Sponge Rubber
- **Flexibility** – Will not break or crack when used in masonry joints
- **Accepted** - Currently used by both residential and commercial contractors
- **PSA** – Available with or without pressure Sensitive Adhesive
- **Economical** – Easily cut and handled on any jobsite, and available on 50' rolls or flat strips

NEOPRENE	
COLOR	BLACK
DENSITY, Apr (lbs/ft ³)	4.5 PCF
Polymer	Neoprene/ SBR
Temp. Resistance Low °F High °F Continuous	-40° +150° F
Compression Deflection 25% PSI Compression Varies with thickness	2-5 PSI
Shore 00 Durometer	45
Water Absorption by weight Max	5%
ASTM Method D1056	(10% Allowed)
Flame Resistance FMVSS302	Pass